fondata nel 1961

CE

GVE INOX

GENERATORI DI VAPORE ELETTRICI
ELECTRIC STEAM BOILERS
GENERATEURS DE VAPEUR ELECTRIQUES
ELEKTRISCHE DAMPFERZEUGER
CALDERA DE VAPOR ELECTRICA

NUOVA OMOLOGAZIONE EUROPEA **PED**

*MADE IN ACCORDANCE WITH **P**RESSURE **E**QUIPMENT **D**IRECTIVE*

MAGNABOSCO SRL

COSTRUZIONE IN ACCIAIO AL CARBONIO
COSTRUZIONE IN ACCIAIO INOX AISI 304 O 316 ED ACCIAI SPECIALI

Modelli GVE da 6 kw a 150 kw

SERIE G.V.E. INOX, monoblocco a funzionamento automatico

- **ESONERABILE DA CONDUTTORE PATENTATO ISPESL ISTITUTO SUPERIORE PER LA PREVENZIONE E SICUREZZA SUL LAVORO (Art. 28 - D.M. 51.5.1974)**
- **ESENTE DA VIGILI DEL FUOCO**
- **ESENTE DA VISITA DI PRIMO IMPIANTO E VISITE PERIODICHE DELL'AGENTE TECNICO ISPESL PRESSO IL CLIENTE**
- **ECONOMIE DI GESTIONE; ALTO RENDIMENTO TERMICO; RAPIDITÀ DI MESSA IN PRESSIONE; MASSIMA SICUREZZA D'ESERCIZIO; FACILITÀ DI MANOVRA E D'INSTALLAZIONE**

I generatori di vapore serie **GVE INOX** producono **VAPORE PULITO senza impurità e senza ossidi**. Questo tipo di generatore viene impiegato nell'industria alimentare, conserviera, farmaceutica, enologica, chimica, petrolchimica ed in altre particolari applicazioni. La pressione è regolabile da 0.5 a 12 bar a seconda del modello. Questo per regolare di conseguenza la temperatura del vapore. Come per il generatore di vapore tipo **GVR INOX**, il rivestimento del generatore ed il serbatoio dell'acqua sono realizzati in **acciaio inox**. Il serbatoio dell'acqua e la pompa possono essere collocati, fino al modello **GVE 72**, sotto il generatore (H1), per occupare il minor spazio possibile. Tutti i generatori sono forniti in versione monoblocco completi di tutte le apparecchiature di comando di controllo, di sicurezza, a richiesta possono essere equipaggiate di quattro ruote per il facile spostamento della macchina, e su richiesta di certificato di esonero fino al modello **GVE 150**, pertanto **sul luogo d'installazione sarà sufficiente collegare gli allacciamenti essenziali e dopo pochi minuti saranno in grado di produrre vapore.**

GVE 18 kw a 18 bar per laboratorio con produttore di acqua calda

GVE 18 kw 18 bar pressure for laboratory with hot water production

GVE 1500 kw, 2000 kg/h di produzione vapore

GVE 1500 kw, 2000 kg/h of steam production

GVE from 6 kw to 150 kw

MADE OF CARBON STEEL
MADE OF STAINLESS STEEL TYPE AISI 304 OR AISI 316 OR OTHER SPECIAL STEEL

G.V.E. ELECTRIC POWERED, stainless steel steam boilers

The steam boilers type ***GVE INOX*** *produce* ***CLEAN STEAM, without impurities and oxides****. These steam boilers are requested to supply steam to the alimentary, cannery, wine processing, chemical, petrolchemical, pharmaceutical industries. The pressure is adjustable from 0.5 to 12 bar in order to have different for steam temperatures. As the steam boiler type* ***GVR inox****, the external covering and the water tank are made in* ***stainless steel****. The water tank and the pump can be located under the boiler in order to save space, up to* ***GVE 72*** *type (H1). Each steam boiler is equipped with all control, safety devices and on request of four wheels for an easy deplacement of the machine.* ***It will be enough to connect the main connections and after few minutes the boiler will produce steam.***

IN ACCORDANCE WITH THE ITALIAN RULES THESE STEAM BOILERS ARE: ON REQUEST FREE FROM THE CONDUCTION OF ISPESL LICENSED STOKER

FREE FROM THE FIREMAN'S TESTS

FREE FROM THE FIRST INSTALLATION INSPECTION AND FROM PERIODIC TESTS OF THE ISPESL INSPECTOR

ECONOMIC; HIGH THERMIC OUTPUT; QUICK RATE REACHING; MAXIMUM SAFETY WORKING; EASY INSTALLATION AND OPERATION

GVE duplex da 90+90 kw

Double GVE 90+90 kw

Modello su ruote
Model on wheels

DATI TECNICI • TECHNICAL DATA

MODELLO *MODEL*	Kw	Produzione vapore Steam production kg/h	hp	Kcal/h	Pressione max *Max working pressure* BAR	DIMENSIONI / *DIMENSIONS mm* A	B	H	H1 *
G.V.E. 6	6	8	0,65	5160	3.5/5/6/8/12	660	770	600	1250
G.V.E. 9	9	12,5	1	8250	3.5/5/6/8/12	660	770	600	1250
G.V.E. 12	12	16	1,5	10320	3.5/5/6/8/12	660	770	600	1250
G.V.E. 18	18	24	2	15480	3.5/5/6/8/12	660	770	600	1250
G.V.E. 24	24	32	2,5	20640	3.5/5/6/8/12	660	770	600	1250
G.V.E. 30	30	40	3,2	25800	3.5/5/6/8/12	660	770	600	1250
G.V.E. 45	45	60	5	38700	3.5/5/6/8/12	660	770	600	1250
G.V.E. 60	60	80	6,5	51600	3.5/5/6/8/12	660	770	600	1250
G.V.E. 72	72	90	7,2	60000	3.5/5/6/8/12	660	770	600	1250
G.V.E. 90	90	120	10	77400	3.5/5/6/8/12	660	1000	800	-
G.V.E. 116	116	160	13	99760	3.5/5/6/8/12	660	1000	800	-
G.V.E. 150	150	200	16	129100	3.5/5/6/8/12	660	1000	800	-
G.V.E. 220	220	300	24	190000	3.5/5/6/8/12	1000	1500	1600	-
G.V.E. 300	300	400	32	258000	3.5/5/6/8/12	1000	1500	1600	-
G.V.E. 380	380	500	40	327000	3.5/5/6/8/12	1500	2500	2000	-
G.V.E. 480	480	650	51	413000	3.5/5/6/8/12	1500	2500	2000	-
G.V.E. 600	600	800	62	516000	3.5/5/6/8/12	1500	2500	2000	-
G.V.E. 750	750	1000	80	645000	3.5/5/6/8/12	1500	2500	2100	-
G.V.E. 1100	1100	1500	120	946000	3.5/5/6/8/12	1500	2500	2100	-
G.V.E. 1500	1500	2000	160	1290000	3.5/5/6/8/12	1500	2500	2100	-
G.V.E. 1850	1850	2500	200	1591000	3.5/5/6/8/12	1800	2500	2200	-
G.V.E. 2200	2200	3000	240	1892000	3.5/5/6/8/12	1800	3000	2200	-

* H1 = Misura con serbatoio sotto la caldaia per risparmiare spazio • ** H1 = Dimension with the tank under the boiler to save space*
Tutti i modelli possono essere costruiti in Fe, AISI 304 o AISI 316 • *All models can be made of carbon steel, AISI 304 or AISI 316*

NUOVA OMOLOGAZIONE EUROPEA PED
MADE IN ACCORDANCE WITH PRESSURE EQUIPMENT DIRECTIVE

Agent:

MAGNABOSCO SRL
QUALITY STEAM BOILERS
SINCE 1960

*36030 **ZUGLIANO** (VI) Italy*
Via Roma, 19
Tel. 0445.330111
Fax 0445.330222
magnabosco@magnabosco.com
www.magnabosco.com

STAMPA SAFIGRAF SCHIO